

Technical data

3412 HT P



Soil Compactors Series 3000
Soil compactor with padfoot drum

H180

HIGHLIGHTS

- > Simple, intuitive and language-neutral operation
- > Electronic machine management Hammtronic
- > 3-point articulation for outstanding traction and off-road mobility
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tilting steering column
- > Excellent view of the machine and the construction site

TECHNICAL DATA 3412 HT P (H180)

Weights

Operating weight with cab	kg	12300
Operating weight with ROPS	kg	12080
Basic weight no cab, without ROPS	kg	11630
Operating weight, max.	kg	13830
Axle load, front/rear	kg	6805/5495
French classific., data/class		43,4/VP3
Load per tyre, rear	kg	2747,5

Machine dimensions

Total length	mm	5705
Total height with cab	mm	3010
Total height with ROPS	mm	2945
Height loading, min.	mm	2325
Wheel base	mm	3015
Total width with cab	mm	2250
Max. working width	mm	2140
Ground clearance, centre	mm	375
Kerb clearance, left/right	mm	465/465
Turning radius, inside	mm	3690
Angle of driving slope, front/rear	°	35/34

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1684
Drum thickness, front	mm	20
Drum type, front		Padfoot
Height of the padfeet	mm	100
Padfeet, number		140

Wheel dimensions

Size of tyres, rear		TR 23.1-26 12 PR
Width over tyres, rear	mm	2130
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Version		TCD 2012 L04 2V
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300
Emission standard		EU Stage IIIA / EPA Tier 3

Drive

Speed, infinitely variable	km/h	0 - 14,0
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	65/70

Vibration

Vibration frequency, front, I/II	Hz	30/40
Amplitude, front, I/II	mm	1,90/0,90
Centrifugal force, front, I/II	kN	256/215

Steering

Steering, type		Articulated steering
----------------	--	----------------------

Tank capacity/Fill capacity

Fuel tank, capacity		290
---------------------	--	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power LW(A), measured	db(A)	103

EQUIPMENT

2 armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Control console with steering column adjustment | Operator's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated operator's platform | Stepless hydrostatic all-wheel drive

OPTIONAL EQUIPMENT

Auxiliary heater | Radio | Tachograph | HCQ Navigator | Protective roof | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Frequency display, vibration | Back-up alarm (reversing) | Telematics interface | Working lights | Rotating beacon | Protective grille for lighting package | Hydraulic hose protection on front frame | Tool kit