

**Technical data** 

# 3516 HT P



**Soil Compactors Series 3000** 

oil compactor with padfoot drun

H176

## **HIGHLIGHTS**

- > 3-point articulation for outstanding traction and off-road mobility
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tilting steering column
- > Excellent view of the machine and the construction site
- > Simple, intuitive and language-neutral operation
- > Electronic machine management Hammtronic

### **TECHNICAL DATA 3516 HT P (H176)**

Weights		
Operating weight with cab	kg	15855
Operating weight with ROPS	kg	15635
Operating weight, max.	kg	17380
Axle load, front/rear	kg	9405/6450
French classific., data/class		59,87/VPM4
Machine dimensions		
Total length	mm	6075
Total height with cab	mm	3010
Height loading, min.	mm	2300
Wheel base	mm	3090
Total width with cab	mm	2270
Ground clearance, centre	mm	375
Turning radius, inside	mm	4360
Angle of driving slope, front/rear	0	35/27
Drum dimensions		
Drum width, front	mm	2140
Drum diameter, front	mm	1684
Drum thickness, front	mm	20
Drum type, front		Padfoot
Height of the padfeet	mm	100
Padfeet, number		140
Wheel dimensions		
Size of tyres, rear		TR 23.1-26 12 PR
Diesel engine		
Manufacturer		DEUTZ
Version		TCD 2012 L06 2V
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
Emission standard		EU Stage IIIA / EPA Tier 3
Drive		
Speed, infinitely variable	km/h	0 - 14,0
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	65/70
Vibration		
Vibration frequency, front, I/II	Hz	30/40
Amplitude, front, I/II	mm	1,86/0,88
Amplitude, front, I/II Centrifugal force, front, I/II	mm kN	1,86/0,88 256/215
Centrifugal force, front, I/II Steering		
Centrifugal force, front, I/II	kN	256/215
Centrifugal force, front, I/II  Steering  Oscillation angle +/- Steering, type	kN	256/215 10
Centrifugal force, front, I/II  Steering  Oscillation angle +/- Steering, type  Tank capacity/Fill capacity	kN °	256/215  10  Articulated steering
Centrifugal force, front, I/II  Steering  Oscillation angle +/- Steering, type  Tank capacity/Fill capacity  Fuel tank, capacity	kN	256/215 10
Centrifugal force, front, I/II  Steering  Oscillation angle +/- Steering, type  Tank capacity/Fill capacity	kN °	256/215 10 Articulated steering

Sound level		
Acoustic power LW(A), measured	db(A)	103

### **EQUIPMENT**

2 armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Control console with steering column adjustment | Operator's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated operator's platform | Stepless hydrostatic all-wheel drive | Handrails on the operator's platform | Dozer blade

### **OPTIONAL EQUIPMENT**

ROPS, rigid | Auxiliary heater | Radio | Protective roof | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Frequency display, vibration | Back-up alarm (reversing) | Working lights | Rotating beacon | Protective grille for lighting package | Hose protection

