

Technical data

HD 10C VV



Tandem rollers Series HD CompactLine

Fandem roller with two vibrating roller drums

H263

HIGHLIGHTS

- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation
- > Clear Side one-sided drum suspension

TECHNICAL DATA HD 10C VV (H263)

Weights		
Operating weight with ROPS	kg	1680
Operating weight, max.	kg	1780
Static linear load, front/rear	kg/cm	8,2/8,7
French classific., data/class		8,7/PV2
Machine dimensions		
Total length	mm	2295
Total height with ROPS	mm	2210
Height loading, min.	mm	1580
Wheel base	mm	1560
Total width	mm	1134
Max. working width	mm	1070
Turning radius, inside	mm	2130
Drum dimensions		
Drum width, front/rear	mm	1000/1000
Drum diameter, front/rear	mm	620/620
Drum thickness, front/rear	mm	12/12
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Diesel engine		
Manufacturer		KUBOTA
Version		D1105
Number of cylinders		3
Power rat. ISO 14396, kW/PS/rpm		16,1/21,9/2600
Power rating SAE J1349, kW/HP/rpm		16,1/21,6/2600
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas level EU		EU Stage V
Exhaust gas level USA		EPA Tier 4
Exhaust gas after-treatment		-
Drive		
Speed, infinitely variable	km/h	0 - 11,0
Climbing ability, vibration on/off	%	30/40
Vibration		
Vibration frequency, front, I/II	Hz	61/48
Vibration frequency, rear, I/II	Hz	61/48
Amplitude, front, I/II	mm	0,38/0,38
Amplitude, rear, I/II	mm	0,38/0,38
Centrifugal force, front, I/II	kN	17/11
Centrifugal force, rear, I/II	kN	17/11
Steering		
Oscillation angle +/-	٥	8
Steering, type		Articulated steering
Sprinkler system		
Water sprinkler, type		Pressure
Tank capacity/Fill capacity		
Fuel tank, capacity	L	33
Water tank, capacity	L	70

Sound level		
Acoustic power LW(A), measured	db(A)	101

EQUIPMENT

12 V socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling with interval switch | Operator's platform with entry from both sides | V-belt protection | Automatic vibration system | Water filtering (triple) | Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, foldable | Additional drive lever, left | Protective roof | Automatic engine-off function | Back-up alarm (reversing) | Working lights | Rotating beacon | Battery isolating switch | Bonnet with sound insulation | Water drain valve | Additional mirror | Tool kit

