

Technical data

HD 110K



Tandem rollers Series HD

Tandem roller with vibrating roller drum and set of tyres

H181

HIGHLIGHTS

- > Excellent view of the machine and the construction site
- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat

TECHNICAL DATA HD 110K (H181)

Weights

Operating weight with cab	kg	9230
Operating weight with ROPS	kg	8965
Operating weight, max.	kg	11890
Static linear load, front	kg/cm	31,5
French classific., data/class		28,9,9,8/VX2.PLO

Machine dimensions

Total length	mm	4600
Total height with cab	mm	3060
Height loading, min.	mm	2360
Wheel base	mm	3400
Total width with cab	mm	1810
Max. working width	mm	1750
Kerb clearance, left/right	mm	790/790
Turning radius, inside	mm	3961

Drum dimensions

Drum width, front	mm	1680
Drum diameter, front	mm	1200
Drum thickness, front	mm	22
Drum type, front		Smooth/non-split
Track offset, left/right	mm	100

Wheel dimensions

Size of tyres, rear		11.00-20
Width over tyres, rear	mm	1620
Number of tyres, rear		4

Diesel engine

Manufacturer		DEUTZ
Version		TCD 2012 L04 2V
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300
Emission standard		EU Stage IIIA / EPA Tier 3

Drive

Speed, working gear	km/h	0-7,4
Speed, transportation gear	km/h	0-14,8
Climbing ability, vibration on/off	%	30/40

Vibration

Vibration frequency, front, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,84/0,49
Centrifugal force, front, I/II	kN	120/99

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Sprinkler system

Water sprinkler, type		Pressure
-----------------------	--	----------

Tank capacity/Fill capacity

Fuel tank, capacity	L	185
Water tank, capacity	L	700

Tank capacity/Fill capacity

Additive tank, capacity	L	22
-------------------------	---	----

Sound level

Sound power level L(WA), guaranteed	db(A)	107
Acoustic power LW(A), measured	db(A)	105

EQUIPMENT

2 drive levers | Amplitude switchable: large/small | Handrails | Lighting package as per road traffic regulations | Operator's platform with entry from both sides | Seat-operating unit, rotatable | Seat-operating unit, rotatable, with armrests and safety belt | Vibration front and rear, switchable single and doubled

OPTIONAL EQUIPMENT

Air conditioning | Tachograph | Fire-extinguisher | Protective roof | Edge pressing and cutting equipment | Frequency regulation | HCQ compaction meter | Speedometer | Back-up alarm (reversing) | Telematics interface | Automatic vibration system | Working lights | Rotating beacon | Locking device | Tool kit