

Technical data

# HD+ 110 VV



**Tandem rollers Series HD+**

Tandem roller with two vibrating roller drums

**H258**

**HIGHLIGHTS**

- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Seat operating unit can be moved and rotated
- > Excellent view of the machine and the construction site
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for even weight distribution and excellent on-centre feel

## TECHNICAL DATA HD+ 110 VV (H258)

## Weights

Operating weight with cab	kg	10965
Operating weight with ROPS	kg	10805
Operating weight, max.	kg	11670
Static linear load, front/rear	kg/cm	32,4/32,9
French classific., data/class		29,6/VT2

## Machine dimensions

Total length	mm	4600
Total height with cab	mm	3050
Height loading, min.	mm	2185
Wheel base	mm	3400
Total width with cab	mm	1800
Max. working width	mm	1850
Kerb clearance, left/right	mm	790/790
Turning radius, inside	mm	5250

## Drum dimensions

Drum width, front/rear	mm	1680/1680
Drum diameter, front/rear	mm	1200/1200
Drum thickness, front/rear	mm	22/22
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	170

## Diesel engine

Manufacturer		DEUTZ
Version		TCD 2012 L04 2V
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300
Emission standard		EU Stage IIIA / EPA Tier 3

## Drive

Speed, working gear	km/h	0-5,0
Speed, transportation gear	km/h	0-11,0
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	35/40

## Vibration

Vibration frequency, front, I/II	Hz	42/50
Vibration frequency, rear, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,81/0,47
Amplitude, rear, I/II	mm	0,81/0,47
Centrifugal force, front, I/II	kN	120/99
Centrifugal force, rear, I/II	kN	120/99

## Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

## Sprinkler system

Water sprinkler, type		Pressure
-----------------------	--	----------

## Tank capacity/Fill capacity

Fuel tank, capacity	L	150
---------------------	---	-----

## Tank capacity/Fill capacity

Water tank, capacity	L	760
----------------------	---	-----

## Sound level

Sound power level L(WA), guaranteed	db(A)	108
Acoustic power LW(A), measured	db(A)	104

## EQUIPMENT

2 water pumps | Foldable scraper | Dashboard with displays, indicator lights and switches | Tilttable dashboard | Spring-mounted driver's seat with armrests and safety belt | Hammtronic - electronic machine management | Seat-operating unit, can be moved and rotated laterally | Track offset | Vibration parameters, adjustable individually | Spray system with spray bars front and rear | Water filtering (triple) | Water tank front and rear, can be filled from both sides | Central water drain

## OPTIONAL EQUIPMENT

Air conditioning | Steering column with comfort exit and tilttable dashboard | Safety belt monitoring device | Additional drive lever, left | HCQ Navigator | Protective roof | Edge pressing and cutting equipment | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Track offset display | Camera system | Rotating beacon