

Technical data

# HD 75K



## Tandem rollers Series HD

Tandem roller with vibrating roller drum and set of tyres

H187

### HIGHLIGHTS

- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Excellent view of the machine and the construction site
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Simple, intuitive and language-neutral operation
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat

## TECHNICAL DATA HD 75K (H187)

## Weights

Operating weight with cab	kg	7335
Operating weight with ROPS	kg	7070
Operating weight, max.	kg	9790
Static linear load, front	kg/cm	23,1
French classific., data/class		17,4.8,6/VX1.PLO

## Machine dimensions

Total length	mm	4340
Total height with cab	mm	2940
Height loading, min.	mm	2260
Wheel base	mm	3200
Total width with cab	mm	1790
Max. working width	mm	1750
Kerb clearance, left/right	mm	780/780
Turning radius, inside	mm	4084

## Drum dimensions

Drum width, front	mm	1680
Drum diameter, front	mm	1140
Drum thickness, front	mm	17
Drum type, front		Smooth/non-split
Track offset, left/right	mm	100

## Wheel dimensions

Size of tyres, rear		11.00-20
Width over tyres, rear	mm	1620
Number of tyres, rear		4

## Diesel engine

Manufacturer		DEUTZ
Version		TD 2011 L04 W
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		55,4/75,3/2500
Power rating SAE J1349, kW/HP/rpm		55,4/74,2/2500
Emission standard		EU Stage IIIA / EPA Tier 3

## Drive

Speed, working gear	km/h	0-6,3
Speed, transportation gear	km/h	0-12,6
Climbing ability, vibration on/off	%	30/40

## Vibration

Vibration frequency, front, I/II	Hz	48/58
Amplitude, front, I/II	mm	0,61/0,33
Centrifugal force, front, I/II	kN	77/63

## Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

## Sprinkler system

Water sprinkler, type		Pressure
-----------------------	--	----------

## Tank capacity/Fill capacity

Fuel tank, capacity	L	140
Water tank, capacity	L	580

## Tank capacity/Fill capacity

Additive tank, capacity	L	11
-------------------------	---	----

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power LW(A), measured	db(A)	104

## EQUIPMENT

2 drive levers | Amplitude switchable: large/small | Handrails | Lighting package as per road traffic regulations | Operator's platform with entry from both sides | Speedometer | Seat-operating unit, rotatable | Seat-operating unit, rotatable, with armrests and safety belt | Vibration front and rear, switchable single and doubled

## OPTIONAL EQUIPMENT

Heating and air conditioning | Protective roof | Edge pressing and cutting equipment | Engine rpm counter | HAMM Temperature Meter (HTM) | Track offset display | Back-up alarm (reversing) | Working lights | Rotating beacon | Water tank cover, lockable