

Technical information

MOBIREX MR 122(i) PRO



Track-mounted impact crushers

Use in natural stone and recycling

MOBIREX PRO

Series

HIGHLIGHTS

- > Frequency-controlled vibrating feeder
- > Independent vibrating double-deck prescreen
- > Option for external power supply (optional)
- > Diesel-electric drive concept

TECHNICAL DATA MR 122(i) PRO

Feeding unit

Feed capacity up to approx. (t/h)	475 ¹⁾
Feed size max. (mm)	1,000 x 625
Feed height (with extension) (mm)	4,600 (5,200)
Hopper volume (with extension) (m ³)	9.5 (20.3)
Width x Length (with extension) (mm)	2,850 x 4,200 (3,500 x 4,200)

Vibrating feeder

Width x Length (mm)	1,000 x 3,500
---------------------	---------------

Prescreening

Type	double-deck heavy-piece screen
Width x Length (mm)	1,200 x 2,300

Side discharge conveyor (optional)

Width x Length (mm)	650 x 6,000
Discharge height approx. (mm)	3,300

Crusher

Impact crusher type	SHB 12/100
Crusher inlet width x height (mm)	1,270 x 1,000
Crusher weight approx. (kg)	18,200
Rotor diameter (mm)	1,300
Crusher drive type, approx. (kW)	electric, 250
Crushing capacity with concrete/rubble up to approx. (t/h)	310 ²⁾
Crushing capacity with asphalt up to approx. (t/h)	265 ³⁾
Crushing capacity with limestone up to approx. (t/h)	350 ⁴⁾

Vibrating extractor

Width x Length (mm)	1,300 x 2,600
---------------------	---------------

Crusher discharge conveyor

Width x Length (extended) (mm)	1,400 x 10,000 (11,500)
Discharge height approx. (extended) (mm)	3,700 (4,200)

Power supply unit

Drive concept	diesel-electric
Drive output of Scania diesel engine (kW)	364 - 368 ⁵⁾
Generator (kVA)	550

Transport⁶⁾

Transport height approx. (mm)	4,110
Transport length approx. (mm)	16,800
Transport width max. (mm)	3,085
Transport weight basic machine - max. equipment (kg)	64,000 - 73,000

- ¹⁾ dependent on the type and composition of the feed material, the feed size, the prescreening, as well as the desired final grain size
²⁾ for final grain size 0 - 45 mm with approx. 10 - 15 % oversize grain
³⁾ for final grain size 0 - 32 mm with approx. 10 - 15 % oversize grain
⁴⁾ for final grain size 0 - 63 mm with approx. 5 - 10 % oversize grain
⁵⁾ depending on the respective exhaust emission standard
⁶⁾ no options

STANDARD FEATURES

Hydraulically foldable feed hopper / Frequency-controlled vibrating feeder / Radio remote control / PLC control with LCD display / Control cabinet, double dust encapsulation, lockable, suspended and with overpressure system / Swivel arm for changing the blow bars / Spray system for dust reduction / Lighting

OPTIONS

Hopper extension / Side discharge conveyor / Electromagnetic separator, permanent magnet or magnet preparation / Extended crusher discharge conveyor (hydraulically foldable) / Preparation for installation of belt scale/Belt covers for side discharge conveyor (aluminium, tarpaulin) / External power supply / Socket 110 V

OPERATING POSITION

