

Technical data

3412 HT



Compactors Series 3000

Compactor with smooth drum

H180

HIGHLIGHTS

- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tilting steering column
- > Excellent view of the machine and the construction site
- > Electronic machine management Hammtronic
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for outstanding traction and off-road mobility

TECHNICAL DATA 3412 HT (H180)

Weights

Operating weight with cab	kg	12200
Operating weight with ROPS	kg	11980
Empty weight without cab, without ROPS	kg	11530
Max. operating weight	kg	15270
Axle load, front/rear	kg	6705/5495
Static linear load, front	kg/cm	31,3
French classification, value/class		42,2/VM3
Wheel load per tyre, rear	kg	2747,5

Machine dimensions

Total length	mm	5705
Total height with cab	mm	2990
Total height with ROPS	mm	2945
Height loading, min.	mm	2325
Centre distance	mm	3015
Total width with cab	mm	2250
Maximum working width	mm	2140
Ground clearance, centre	mm	375
Kerb clearance, left/right	mm	465/465
Turning radius, inside	mm	3690
Slope angle, front/rear	°	31/34

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1504
Drum thickness, front	mm	30
Drum type, front		Smooth

Tyre dimensions

Tyre size, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2130
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 2012 L04 2V
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power SAE J1349, kW/HP/rpm		100,0/134,0/2300
Exhaust emission standard		EU Stage IIIA / EPA Tier 3

Travel drive

Speed, infinitely variable	km/h	0 - 14,0
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	58/63

Vibration

Vibration frequency, front, I/II	Hz	30/40
Amplitude, front, I/II	mm	1,91/0,90
Centrifugal force, front, I/II	kN	256/215

Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	290
---------------------	---	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

2 x armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Driver's platform with steering column adjustment | Driver's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated driver's platform | Stepless hydrostatic all-wheel drive

OPTIONAL EQUIPMENT

Auxiliary heater | Radio | Tachograph | HCQ Navigator | Protective roof | Padfoot shells | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Frequency display, vibration | Back-up alarm | Telematics system | Working spotlights | Rotating beacon | Protective grille for lighting package | Hydraulic hose protection on the front frame | Tool kit